

PTFE Coated Chemical Resistant Vacuum Pump



Features

- ▶ **Chemical resistance & effective**
Applied with PTFE-coated diaphragm and pump head with FKM valves, Rocker 400C / 410C pumps are adequate to work in milder chemical gases and be cost-effective at the same time.
- ▶ **Oil-free & care-free**
Rocker 400C / 410C pumps are driven by diaphragm that needs no lubricant, making them maintenance-free and oil-mist-free.
- ▶ **Minimized vibration & quiet**
Superior weight distribution and assemblies minimize the vibration and noises and maximize stability.
- ▶ **Overheat protection**
All Rocker 400C / 410C pumps are equipped with overheat protection device that shuts down when overheated and resumes once cooled down, making the pumps safer and long-lasting.
- ▶ **International certification**
CE certification
IP 30 protection
RoHS certification
- ▶ **One-Year Warranty**



Rocker 400C



Rocker 410C

* For aggressive solvents and solutions, please refer to Chemker pumps.

Applications

- ▶ Solvent purification
- ▶ Gel dryer
- ▶ Vacuum desiccator
- ▶ Vacuum filtration

Ordering Information

189400-11(22)
Rocker 400C, PTFE Coated Chemical Resistant Vacuum Pump
AC110V, 60Hz (AC220V, 50Hz)

189410-11(22)
Rocker 410C, PTFE Coated Chemical Resistant Vacuum Pump
AC110V, 60Hz (AC220V, 50Hz)

Specification

Model	Rocker 400C		Rocker 410C	
PERFORMANCE DATA				
Max. vacuum	99 mbar abs.		25 mbar abs.	
Max. flow rate	34 L/min @60Hz	31 L/min @50Hz	23 L/min @60Hz	20 L/min @50Hz
Hose barb	ID8		ID8	
Noise level	52 dB		52 dB	
Net weight	5.7 Kg		5.6 Kg	
Dimension (LxWxH)	31 x 14 x 20 cm		31 x 14 x 20 cm	
ELECTRICAL DATA				
Voltage	110V	220V	110V	220V
Frequency	50 / 60Hz		50 / 60Hz	
Max. power	100W (1/6 HP)	80W (1/6 HP)	100W (1/6 HP)	80W (1/6 HP)
Max. current	1.0A	0.4A	1.0A	0.4A
Safety	Overheat Protection		Overheat Protection	
OTHER DATA				
Equipped with	Glass moisture trap Vacuum regulator		Glass moisture trap Vacuum regulator	