

VioLab

PC 50

pH - mV - ORP - Cond - TDS - Temperature

PC 60

pH - mV - ORP - Cond - TDS - Salinity - Temperature -
GLP - Data Logger - RS 232 Printer



MADE IN ITALY

The first electrochemical instrumentation line completely conceived, designed and produced in Italy is here.

PC 50 *VioLab*

pH - mV - ORP - Cond - TDS - Temperature

Professional bench meters with **innovative backlit high definition colored LCD display**, with possibility of brightness adjustment.

Management of DHS digital sensors.

Possibility to **select the parameters** to show on the display.

The **step by step guide in setup and calibration** allows a simple and immediate use of the device.

Automatic pH calibration with USA and NIST buffers, up to 3 points and 2 points defined by the user.

Automatic ORP calibration on 1 point.

Automatic conductivity calibration up to 5 points (84; 147; 1413 μ S e 12,88; 111,8 mS) and 1 point custom.

Automatic resolution, reference temperature from 15 to 30 °C, and selectable cell constant (C= 0,1; 1; 10).

Indication of the calibrated points, with icons.

Measurement **stability indication** and possibility to select 3 stability levels.

All operations are constantly monitored and shown to the operator by the **colored LED** above the display and **self-diagnosis messages**.

DHS *Digital High Sensor*

Instruments compatible with DHS digital sensors, for **maximum performance and safety**



Connections PC 50 VioLab

The **LED indicator** allows you to keep always under control the state of the measurement



NEW DISPLAY

The new high-resolution display shows all the useful information, including the buffer used for calibration and the stability icon. Through guided procedures it makes the user experience intuitive and safe, as well as extremely performing.

How to order:

PC 50 VIOLAB

code

Complete with **digital pH electrode XS 201 T DHS** and **conductivity cell 2301T (C=1)**, both with integrated temperature sensor

50103892

Complete with **pH electrode XS 201 T** and **conductivity cell 2301T (C=1)**, both with integrated temperature sensor

50103902

With **conductivity cell 2301T (C=1)**, accessories, cable S7-BNC and temperature sensor NT 55 Without pH electrode

50103912

Inside the box:

Electrode holder stand, pH and conductivity buffer solutions, power supply and instructions for use.

PC 60 *VioLab*

pH - mV - ORP - Cond - TDS - Salinity - Temperature - GLP - Data Logger

... only on PC 60 VioLab

- GLP function:** Date and time, recall of calibration data and function "Calibration due".
- Data logger up to 1000 savings,** manual and automatic, PC connect via micro-USB.
- Data-Link software** available from www.xsinstruments.com.
- RS 232 external printer connection**



Connections PC 60 VioLab



Only **6 buttons** to easily manage all the functions of the instrument.

#	Date	Time	Value	M.U.	Temp	M.U.	MTC/ASC	DHG
1	16/01/2020	14:53:40	7,00	pH	25,0	°C	MRC	
2	16/01/2020	14:53:40	7,00	pH	25,0	°C	MRC	
3	16/01/2020	14:53:42	7,00	pH	25,0	°C	MRC	
4	16/01/2020	14:53:43	7,00	pH	25,0	°C	MRC	
5	16/01/2020	14:53:44	9,54	pH	25,0	°C	MRC	
6	16/01/2020	14:53:45	10,51	pH	25,0	°C	MRC	
7	16/01/2020	14:53:46	10,51	pH	25,0	°C	MRC	
8	16/01/2020	14:53:47	10,51	pH	25,0	°C	MRC	
9	16/01/2020	14:53:48	10,51	pH	25,0	°C	MRC	
10	16/01/2020	14:53:50	6,40	pH	25,0	°C	MRC	
11	16/01/2020	14:53:51	6,40	pH	25,0	°C	MRC	
12	16/01/2020	14:53:51	6,40	pH	25,0	°C	MRC	

DATA LINK +

The software allows remote control of the instrument in measure mode, shows all information relating to the instrument and calibrations, data export at the end of the analysis, (also in Excel and PDF format), and the display of measurements in the table and in graphic.

How to order:

PC 60 VIOLAB

Complete with **digital pH electrode XS 201 T DHS** and **conductivity cell 2301T (C=1)**, both with integrated temperature sensor

code

50103942

Complete with **pH electrode XS 201 T** and **conductivity cell 2301T (C=1)**, both with integrated temperature sensor

50103952

With **conductivity cell 2301T (C=1)**, accessories, cable S7-BNC and temperature sensor NT 55 Without pH electrode

50103972

Inside the box:

Electrode holder stand, pH and conductivity buffer solutions, USB cable, power supply and instructions for use.

Data sheet

	PC 50 VioLab	PC 60 VioLab
pH Measuring range	0 ... 14,00	-2...16,00
Resolution / Accuracy	0.1, 0.01 / ± 0.02	
Calibration points	1...3 Auto + 2 custom	
Buffer recognized	USA, NIST, 2 custom	
DHS sensors recognition	Yes	
mV Measuring range	-1000 ... +1000	-1000 ... +1900
Resolution	1	0.1 / 1
ORP Calibration point	1 point = 475 mV	
COND Measuring range	0,00 ... 200 mS	
Resolution	0,01 - 0,1 - 1 µS / mS (automatic)	
Accuracy	± 2% f.s.	
Calibration points	1...5	
Buffer recognized	84 µS - 147 µS -1413 µS - 12,88 mS - 111,8 mS + 1 User	
Reference temperature	15 ... 30 °C	
Temperature coefficient	0,00 ... 10,00 % / °C	
TDS Measuring range	0,1 mg/l ... 200 g/l	
TDS Factor	0.40 ... 1.00	
Salinity Measuring range	-	0,1 ppm ... 100 ppt
Temperature Measuring range	0,0...100,0 °C	-10,0...110,0 °C
Resolution / Accuracy	0,1 / ± 0,5 °C	
Temperature compensation	0,0...100,0 °C	
System: GLP	-	Yes
Calibration due	-	Yes
Calibration point indication	Yes	
Calibration report	Yes	Yes, printable
Stability filter	Low - Nor - High	
Internal memory	-	1000 Data
Display	high definition backlight colored LCD	
Brightness	Manual	
IP protection	IP 54	
Output	-	Micro USB and RS 232
Power supply	5 V power adapter	
Electrical tension	100 ... 240 V	
Working conditions	0 ... +45 °C	
Dimensions / Weight	160 x 140 x 45 mm / 380 g	



ST 10 magnetic stirrer
cod: 50000132



RS 232 printer
cod: 50001502



201 T DHS
Digital pH electrode with DHS technology. Temperature sensor integrated. Plastic body for general use. Maintenance free. pH: 0...14 - T: 0...60 °C
cod: 32200103



2301 T
Conductivity cell, Temperature sensor integrated
Cable 1 m
Measuring range: 10µS...200 mS
cod: 50004002



Distributed by:

